



Trendy softshell jacket

Functional 3-layer-fabric with TPU membrane
 Wind- and water-repellent (5,000 mm water column), breathable and permeable to water vapour (1,000 g/m²/24h)
 Non-taped seams
 Inside made of micro fleece, mesh lining at the front
 2 zipped side pockets, Zip in front lining for embroideries
 JN135: 1 vertical breast pocket with zip
 JN137: lightly waisted
 JN135K: Fashionable, reflective piping at the front, back and on the sleeves

Fabric: Outer fabric (330 g/m²): 95% polyester, 5% elastane

Country of origin: China

Customs tariff number: 62024010

Care instructions:



Partner article:



Men's Softshell Jacket
 Art-Nr.: JN135

Available colours

	S	M	L	XL	XXL
Weight in g	566 g	609 g	643 g	657 g	708 g
VPE (Pcs. per inner packaging / pcs. per outer packaging)	1/10	1/10	1/10	1/10	1/10

Measurements in cm	S	M	L	XL	XXL
1/2 chest	45,00 cm	49,00 cm	53,00 cm	57,00 cm	62,00 cm
1/2 waist width	43,00 cm	47,00 cm	51,00 cm	55,00 cm	59,00 cm
1/2 bottom width	47,00 cm	51,00 cm	55,00 cm	59,00 cm	64,00 cm
front length from shoulder	60,00 cm	61,00 cm	63,00 cm	65,00 cm	67,00 cm
length back from shoulder	64,00 cm	65,00 cm	67,00 cm	69,00 cm	71,00 cm
sleevelength incl. shoulder	73,00 cm	74,00 cm	75,00 cm	76,00 cm	77,00 cm

Available colours

 aqua (2925C)
 carbon (433U)
 olive (5743U)

 black (blackC)
 navy (296C)
 red (187C)

 brown (476C)
 off-white (off-white)



Softshell

Softshell with TPU membrane consists of three layers. Due to the microporous TPU membrane as middle layer the material is water-proof, wind-proof and breathable at the same time.



Breathable-Permeable to water vapour

Functional textiles must have the ability to transport moisture from the skin to the fabric surface as fast as possible. Permeability shows how much steam in grams can evaporate on a surface of 1 m² within 24 hours. The higher this figure, the more breathable the textile is.



Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.